

General Spec Sheet:

22" x 34" (559mm x 864mm) Half Round Vent


The 22" x 34" (559mm x 864mm) Half Round Vent is a functional and decorative vent designed to provide unforced free airflow ventilation of attics or similar spaces when used in conjunction with proper soffit ventilation practices. Local ventilation codes apply when installing this unit.

FEATURES:

- Easy to install on all types of exteriors
- Single unit body construction of vent housing
- J-Channel eliminated
- Double baffles for increased weather resistance
- Fully screened for complete insect protection
- Finish trim ring adjusts for a range of siding thickness


SPECIFICATIONS:

Material:	Vent	UV stabilized copolymer; colour moulded in; .100" (2.54mm) nominal wall
	Ring	UV stabilized copolymer; colour moulded in; .100" (2.54mm) nominal wall
	Baffle	Black PP; .025" (.635mm) wall
	Screen	Fiberglass; 18" x 16" (457mm x 406mm)
		Paintable/Stainable HIPS available
Fabrication:		Single piece moulded unit
		Baffle and screen sealed to interior side of unit
		Trim ring single piece moulded unit
Attachment:		Screw or nail directly to any surface
Packaging:		1 assembly per box
Vent Free Area:		100 sq. in. (64516 sq. mm)
Rough Opening:		16" x 24" (406mm x 610mm)
U.S. Patent No:		4,875,318; 5,349,799
Can. Patent No:		1,280,024
Dimensions:		



22" x 34" (559mm x 864mm) Half Round Vent

Net Free Area: 100 sq. in. (64516 sq. mm)



22" x 34" (559mm x 864mm) Half Round Vent
Net Free Area: 100 sq. in. (64516 sq. mm)

Note: Complete installation instructions are included with each product.




HALF-ROUND INSTALLED



In most cases, the rough opening can be cut directly into the sheathing. However, if a non structural sheathing is used, such as an insulating foamboard, it is recommended that the opening be framed in.

EXAMPLE OF ROUGH OPENING



* Rough opening refers to the minimum amount of unobstructed wall opening needed to maintain the Net Free Area.