

DuPont™ Tyvek® CommercialWrap® D

Durable Air and Water-Resistive Barrier Engineered to Improve Drainage and Stand Up to the Commercial Job Site



FEATURES/BENEFITS

Description

DuPont™ Tyvek® CommercialWrap® D offers superior drainage and durability for commercial buildings. It features a specially engineered surface texture that provides enhanced water drainage under a wide variety of facades in climates that may require additional drainage.

Tyvek® CommercialWrap® D is made from 100% flash spunbonded high-density polyethylene fibers which have been bonded together by heat and pressure, without binders or fillers, into a tough durable sheet structure. Additives have been incorporated into the polyethylene to provide ultraviolet light resistance.

Air and Water Barrier Performance

- Offers the ideal combination of enhanced drainage, air and water holdout plus vapor permeability.
- Air Barrier Association of America evaluated to exceed ABAA, ASHRAE 90.1 and IECC air leakage requirements when tested in accordance with ASTM E2357.
- Offers > 98% drainage efficiency when tested in accordance with ASTM E2273.
- Offers high tear-resistance and high wind-load-resistance to help stand up to commercial construction site conditions.
- Withstands up to nine months of UV exposure.

- ASTM E2556, Type II Compliant – Standard Specification for Vapor Permeable Flexible Sheet Water-Resistive Barriers Intended for Mechanical Attachment.

Available Sizes

Tyvek® CommercialWrap® D is available in the following roll sizes:

- 5' x 200' (1.5 x 61 m)
- 10' x 125' (3.1 x 38.1 m)

Sustainable Solutions

Tyvek® CommercialWrap® D may contribute toward LEED® points in the areas of Energy and Atmosphere (EA): Optimizing the Building Envelope and Indoor Environmental Air Quality (EQ): Construction IAQ Management Plan and Low Emitting Materials. In addition, the use of a continuous air barrier is a prerequisite for LEED® applications requiring compliance with ASHRAE 90.1.

By helping to effectively seal the building envelope, Tyvek® CommercialWrap® D helps to reduce the amount of energy required for heating and cooling.

Complete System

Tyvek® CommercialWrap® D can be integrated with DuPont Self-Adhered Flashing Products and Tyvek® Fluid Applied Products to offer seamless protection for wall systems that require mechanically fastened and fluid applied air and water barriers.

PROPERTIES

Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact your local DuPont™ Tyvek® Specialist before writing specifications around this product. Product properties are as follows:

Test Method	Property	Typical Value	Units
ASTM E2357	Air Penetration Resistance	<0.04	cfm/ft ² @ 1.57 psf
Gurley Hill (TAPPI T-460)	Air Penetration Resistance	>750	sec/100cc
ASTM E1677	Air Penetration Resistance	Type 1	cfm/ft ² @ 1.57 psf
ASTM E2178	Air Penetration Resistance	.001	cfm/ft ² @ 1.57 psf
ASTM E283	Wall Assembly Air Penetration Resistance	<0.04	cfm/ft ² @ 1.57 psf
ASTM E96-05	Water Vapor Transmission	212	Method B g/m ² -24 hrs
E96-05	Water Vapor Transmission	30	Method B (perms)
AATCC 127	Water Penetration Resistance	235	cm
ASTM E331	Wall Assembly Water Penetration Resistance	No leakage	Tested to 15 psf
ICC-ES AC 24 Section 6.11 ASTM E2273 ICC-ES AC 235 Section 4.5	Drainage Efficiency	Pass >98 Pass	%
TAPPI T-410	Basis Weight	2.4	oz/yd ²
ASTM D882	Breaking Strength	33/41	lbs/in
ASTM D1117	Tear Resistance	6/9	lbs
ASTM E84	Surface Burning Characteristics	15 Class A	Flame Spread Index Class
ASTM E84	Surface Burning Characteristics	25 Class A	Smoke Developed Index Class
ASTM E1354	Peak Heat Release Rate	<100	kW/m ²
	Total Heat Release/Area	<5	MJ/m ²
	Effective Heat of Combustion	<10	MJ/kg
NFPA 285	Flame Propagation/Multiple Assemblies	-	Pass
-	Ultra Violet Light Exposure (UV)	270 9	Days Months

Test results shown represent roll averages. Individual results may vary either above or below averages due to normal manufacturing variations, while continuing to meet product specifications.

WARNING: DuPont™ Tyvek® is combustible and should be protected from an open flame and other high heat sources. If the temperature of DuPont™ Tyvek® reaches 750°F (400°C), it will burn and the fire may spread and fall away from the point of ignition.



**For more information visit us at
building.dupont.com
or call 1-833-338-7668**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.