

# MATERIAL SAFETY DATA SHEET

GC65100/200/300  
05 00

DATE OF PREPARATION  
Nov 6, 2015

## SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NUMBER**

GC65100/200/300

**PRODUCT NAME**

Geocel® 2310® Tripolymer Brushable Repair Coating, Clear

**MANUFACTURER'S NAME**

Geocel Products Group  
A Business Unit of The Sherwin-Williams Company  
101 W. Prospect Avenue  
Cleveland, OH 44115

**Telephone Numbers and Websites**

<b>Product Information</b>	(800) 348-7615 www.geocelusa.com
<b>Regulatory Information</b>	(216) 566-2902
<b>Medical Emergency</b>	(216) 566-2917
<b>Transportation Emergency*</b>	(800) 424-9300
<i>*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)</i>	

## SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
2	1330-20-7	<b>Xylene</b>		
		ACGIH TLV	100 PPM	5.9 mm
		ACGIH TLV	150 PPM STEL	
		OSHA PEL	100 PPM	
		OSHA PEL	150 PPM STEL	
15	64742-95-6	<b>Light Aromatic Hydrocarbons</b>		
		ACGIH TLV	Not Available	3.8 mm
		OSHA PEL	Not Available	
3	98-82-8	<b>Cumene</b>		
		ACGIH TLV	50 PPM	10 mm
		OSHA PEL	50 PPM	
2	526-73-8	<b>1,2,3-Trimethylbenzene</b>		
		ACGIH TLV	Not Available	0.931 mm
		OSHA PEL	Not Available	
6	108-67-8	<b>1,3,5-Trimethylbenzene</b>		
		ACGIH TLV	25 PPM	2 mm
		OSHA PEL	25 PPM	
23	95-63-6	<b>1,2,4-Trimethylbenzene</b>		
		ACGIH TLV	25 PPM	2.03 mm
		OSHA PEL	25 PPM	

## SECTION 3 — HAZARDS IDENTIFICATION

**ROUTES OF EXPOSURE**

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.

**EFFECTS OF OVEREXPOSURE**

**EYES:** Irritation.  
**SKIN:** Prolonged or repeated exposure may cause irritation.  
**INHALATION:** Irritation of the upper respiratory system.

**HMIS Codes**

<b>Health</b>	2
<b>Flammability</b>	2
<b>Reactivity</b>	0

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.  
Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the liver
- the urinary system

- the reproductive system

**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE**

None generally recognized.

**CANCER INFORMATION**

For complete discussion of toxicology data refer to Section 11.

**SECTION 4 — FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.

**SKIN:** Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** Do not induce vomiting. Get medical attention immediately.

**SECTION 5 — FIRE FIGHTING MEASURES****FLASH POINT**

109 °F PMCC

**LEL**

0.7

**UEL**

7.0

**FLAMMABILITY CLASSIFICATION**

Combustible, Flash above 99 and below 200 °F

**EXTINGUISHING MEDIA**

Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS**

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES**

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 — ACCIDENTAL RELEASE MEASURES****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

**SECTION 7 — HANDLING AND STORAGE****STORAGE CATEGORY**

DOL Storage Class II

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Contents are COMBUSTIBLE. Keep away from heat and open flame.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

**SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION****PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES**

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION**

Wear safety spectacles with unperforated sideshields.

**OTHER PRECAUTIONS**

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

**SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES**

<b>PRODUCT WEIGHT</b>	7.66 lb/gal	917 g/l
<b>SPECIFIC GRAVITY</b>	0.92	
<b>BOILING POINT</b>	281 - 360 °F	138 - 182 °C
<b>MELTING POINT</b>	Not Available	
<b>VOLATILE VOLUME</b>	53%	
<b>EVAPORATION RATE</b>	Slower than ether	
<b>VAPOR DENSITY</b>	Heavier than air	
<b>SOLUBILITY IN WATER</b>	Not Available	
<b>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)</b>		
	3.90 lb/gal	468 g/l
	3.90 lb/gal	468 g/l
	Less Water and Federally Exempt Solvents	
	Emitted VOC	

**SECTION 10 — STABILITY AND REACTIVITY****STABILITY — Stable****CONDITIONS TO AVOID**

None known.

**INCOMPATIBILITY**

None known.

**HAZARDOUS DECOMPOSITION PRODUCTS**

By fire: Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION**

Will not occur

**SECTION 11 — TOXICOLOGICAL INFORMATION****CHRONIC HEALTH HAZARDS**

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**TOXICOLOGY DATA**

CAS No.	Ingredient Name			
1330-20-7	Xylene	LC50 RAT LD50 RAT	4HR	5000 ppm 4300 mg/kg
64742-95-6	Light Aromatic Hydrocarbons	LC50 RAT LD50 RAT	4HR	Not Available Not Available
98-82-8	Cumene	LC50 RAT LD50 RAT	4HR	Not Available 1400 mg/kg
526-73-8	1,2,3-Trimethylbenzene	LC50 RAT LD50 RAT	4HR	Not Available Not Available
108-67-8	1,3,5-Trimethylbenzene	LC50 RAT LD50 RAT	4HR	Not Available Not Available
95-63-6	1,2,4-Trimethylbenzene	LC50 RAT LD50 RAT	4HR	Not Available Not Available

## SECTION 12 — ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

No data available.

## SECTION 13 — DISPOSAL CONSIDERATIONS

### WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

## SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

### US Ground (DOT)

May be Classed as a Combustible Liquid for U.S. Ground.  
UN1263, PAINT, 3, PG III, (ERG#128)

### DOT (Dept of Transportation) Hazardous Substances & Reportable Quantities

Xylenes (isomers and mixture) 100 lb RQ

### Bulk Containers may be Shipped as (check reportable quantities):

UN1263, PAINT, 3, PG III, (ERG#128)

### Canada (TDG)

May be Classed as a Combustible Liquid for Canadian Ground.  
UN1263, PAINT, 3, PG III, (ERG#128)

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.  
UN1263, PAINT, 3, PG III, MARINE POLLUTANT, (43 C c.c.),  
(MESITYLENE), EmS F-E, S-E

### IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.  
UN1263, PAINT, 3, PG III, MARINE POLLUTANT, (43 C c.c.),  
(MESITYLENE), EmS F-E, S-E

### IATA/ICAO

UN1263, PAINT, 3, PG III

## SECTION 15 — REGULATORY INFORMATION

### SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
1330-20-7	Xylene	2	
98-82-8	Cumene	3	
95-63-6	1,2,4-Trimethylbenzene	23	

### CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.