

• TRUSTED QUALITY SINCE 1921 •



# ROOF ACCESSORY COATING

## DESCRIPTION AND USES

Rust-Oleum® Roof Accessory Coating creates a durable, weather-resistant finish that can be applied to stacks, vents and other roof penetrations. Roof Accessory Coating protects and matches a variety of roof accessories and can be applied to wood, metal, masonry and plastic.

**NOTE:** Not for use on galvanized steel.

## PRODUCT FEATURES

- Protects and matches roof accessories
- Adheres to metal, plastic, masonry and wood
- Durable weather resistant finish

## PRODUCTS

SKU	DESCRIPTION (12 Oz. Aerosol)
285217	Weathered Wood
285222	Rustic Slate
302123	Dark Gray
285225	Shakewood
302125	Espresso Shake
285227	Carbon Black
313815	Red Tile
314061	Cedar

## PRODUCT APPLICATION

### SURFACE PREPARATION

Remove all dirt, grease, oil, and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN YOUNG CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## PRODUCT APPLICATION (cont.)

### APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use when the temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or on galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold the can upright 10-16" from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface and keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart.

### DRY & RECOAT TIMES

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Dries to the touch in 20 minutes, to handle in 1 hour and is fully dry in 24 hours. Apply a second coat or clear coat within 1 hour or after 48 hours. Apply a clear coat in 2-3 light coats a few minutes apart.

**NOTE:** On plastic, maximum paint adhesion and durability is achieved in 5-7 days.

### CLEAN-UP

When finished spraying, wipe off tip before storing. Clean up wet paint with xylene or mineral spirits. Dispose of empty can in recycle pickup. Do not burn or place in home trash compactor.

### CLOGGING

If valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not stick pin or other object into the stem.

• TRUSTED QUALITY SINCE 1921 •	<b>TECHNICAL DATA</b>	<b>ROC-72</b>
<b>RUST-OLEUM®</b>		<b>ROOF ACCESSORY COATING</b>

**PHYSICAL PROPERTIES**

		ROOF ACCESSORY COATING
<b>Resin Type</b>		Modified Alkyd Resin
<b>Pigment Type</b>		Varies with color
<b>Solvents</b>		Acetone, Hydrotreated Light Distillate, n-Butane, Naphtha, Xylene
<b>MIR</b>		0.95 Max
<b>Fill Weight</b>		12 ounces
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		1.0-2.5 mils (25-62.5μ)
<b>Wet Film to Achieve DFT</b>		Varies depending on porosity and texture of surface
<b>Practical Coverage at Recommended DFT</b>		10-12 sq. ft./can (0.9-1.1 m <sup>2</sup> /can)
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	20 minutes
	<b>Handle</b>	1 hour
	<b>Recoat</b>	Within 1 hour or after 48 hours
<b>Dry Heat Resistance</b>		200°F (93°C)
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-141°F (-96°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.