



Ladder Stability Anchor Part #70827

**Do not throw away these instructions! Read and understand these instructions before using this device.
For any questions, please call (404) 344-0000.**

Compliant with OSHA 1910 and
OSHA 1926 Subpart M regulations.

Materials: aluminum, polyester, nylon, & Velcro.

Ladder Stability Device comes with (2) 48" Velcro straps.

The Ladder Stability Anchor functions to secure a ladder against the structure, and reduce the possibility of the bottom of the ladder kicking out as a result of transitions between the ladder and the structure.

1. Secure the Ladder Stability Anchor (LSA) to a fascia board or other horizontal structural member.
2. Attach hook and loop to LSA and wrap around the rung of the ladder to secure ladder from movement. Be sure that the LSA attaches within the top 4 rungs of the ladder.

User must inspect Ladder Stability Anchor prior to each use. Competent Person must inspect Ladder Stability Device at least every 6 months.



Step 1



Step 2

 **WARNING:** This product can expose you to chemicals including Nickel, which is known to the State of California to cause cancer. For more information go to: www.P65Warnings.ca.gov



Safety Products Division
605 Stonehill Drive SW
Atlanta, Georgia 30336
800-241-1806 • 404-344-0000

www.tiedown.com
ISO 9001:2015 Certification
Intellectual property of TIE DOWN Inc.
©2020 TIE DOWN, Inc.
Instruction #08384 (E1848 Rev. 5/10/21)