



**3-IN-ONE®**

# 3-IN-ONE® Motor Oil Technical Data Sheet

## Typical Physical Characteristics – USA

**Color & Appearance:** Light amber liquid  
**Odor:** Faint citronella odor  
**Odor Threshold:** Not established  
**pH:** Not applicable  
**Melting/Freeze Point:** Not established  
**Specific Gravity at 15°C:** 0.86 – 0.94  
**Boiling Point/Range:** >536°F  
**Vapor Density:** Greater than 1 (air=1)  
**Relative Density:** 0.866 - 0.940 @ 20°C  
**Solubilities:** Insoluble in water  
**Flash Point:** >305°F Tag Open Cup  
**Evaporation Rate:** Not established  
**Flammability (solid, gas):** Not applicable  
**VOC:** 0%  
**Partition Coefficient; n-octanol/water:** Not established  
**Autoignition Temperature:** Not established  
**Decomposition Temperature:** Not established  
**Viscosity:** 68mm<sup>2</sup> /s @ 40°C  
**Pour Point:** Not established  
**Flammable Limits:** Not established  
**Vapor Pressure:** <0.1 mmHg @ 20°C

## Product Features

3-IN-ONE® Motor Oil is a SAE 20 special blend of high-grade oils engineered for 1/4 HP motors or larger. This long-lasting formula is great as an electric motor oil and lubricant and can also be used to maintain sewing machines, fans, drills, lawn tools, and more. In fact, 3-IN-ONE® Motor Oil is ideal for a variety of home maintenance projects, as it reduces friction that leads to wear and tear, improves overall performance, and extends motor life. And, let's not forget the Marksman Spout and easy-squeeze bottle—with these built-in features, you get a quick and precise, no-mess application, every time. Ideal to use for lubricating moving parts, pivot points, and bearings on small to larger motors found in sewing machines, fans, lawnmowers and trimmers, drills, chainsaws, and other tools.

UPC#: 0 79567 10045 4



## 3-IN-ONE Motor Oil and the Environment

- 3-IN-ONE Motor Oil Product does not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated diphenylether complying with the restricted substances listed in Article 4(1) of the RoHS Directive.
- 3-IN-ONE Motor Oil Product contains no ingredients requiring California Prop 65 labeling such as benzene or toluene.
- 3-IN-ONE Motor Oil Product complies with California VOC regulations.



**HDPE**

Recycle where  
allowed

## Fluid Properties

**Working Temperature Range:** -15°F to 300°F

### Surface Cautions:

Always test surfaces first. Do not immerse rubber parts in product.

### Surface Compatibility:

Safe on multiple surfaces including metal, plastic and rubber.

**First Aid Measures**

**Ingestion (Swallowed):** While aspiration is unlikely due to viscosity, DO NOT induce vomiting. Call physician, poison control center or the WD-40 Company Safety Hotline at 1-888-324-7596 immediately.

Contains petroleum distillates, Avoid frequent or prolonged contact with skin.

**REGULATORY****U.S. Federal Regulations:**

**CERCLA 103 Reportable Quantity:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**SARA TITLE III:**

**Hazard Category For Section 311/312:** Non-Hazardous

**Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

**Section 302 Extremely Hazardous Substances (TPQ):** None

**EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory.

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):** This product does not require a California Proposition 65 warning.

**VOC Regulations:** This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.



**WD-40 COMPANY**  
9715 Businesspark Avenue, San Diego, CA 92131 U.S.A  
WD-40 Company Safety Hotline 1-888-324-7596  
3InOne.com

© July 2021 WD-40 Company  
3N1MotorOilTDS