

TECHNICAL DATA SHEET

WD-40[®] Specialist[®] SPRAY & STAY GEL LUBRICANT



PRODUCT DESCRIPTION

WD-40 Specialist Spray & Stay Gel Lubricant – No-Drip Formula. A unique gel lubricant that sprays on thick and won't run, drip or make a mess. Provides 12x longer-lasting lubrication and prevents rust and corrosion for up to 1 year. No-fling makes it excellent for moving parts that need lubrication.

APPLICATIONS

- CHAINS
- CABLES
- GEARS
- ROLLERS
- BEARINGS
- VERTICAL SURFACES
- MOVING PARTS

FEATURES & BENEFITS

Unique, Thick Gel Lubricant

12x Longer-Lasting Lubrication*

Prevents rust for up to 1 year**



50-state VOC compliant

Effective in a temperature ranges from -100°F to 500°F

No Drip/No Mess

PHYSICAL and CHEMICAL PROPERTIES

Boiling Point (initial):	221-271°C (430-520°F)	Density:	0.89g/mL
Solubility in Water:	Insoluble	pH:	Not Applicable
Vapor Pressure:	Not established	Vapor Density:	>1
		VOC:	24.5%
Coefficient of Water/Oil Distribution:	Not Established	Appearance/Odor:	Light amber liquid with a mild petroleum odor.
Flash Point:	>69°C (-156°F) (CC ASTM D3828)	Flammable Limits:	LEL: 0.6% UEL: 8.0%

PERFORMANCE RESULTS

4 BALL WEAR (ASTM D4172)

This test measures the wear protection of a fluid on a metal surface. A steel ball is pressed with force against three stationary steel balls and is rotated at 1200 rpm for 60 minutes. WD-40 Specialist Protective Spray & Stay Gel Lubricant lives up to its name as it lubricates and protects the steel ball.

WD-40 Specialist	.39 mm
WD-40 Multi-Use Product	.60 mm

* RESULTS SHOW DEPTH OF SCAR IN MILLIMETERS. LOWER IS BETTER.

DIRECTIONS

SHAKE CAN WELL (20-25 Seconds) before EACH spray. Flip straw up for STREAM or down for SPRAY. Make sure there is a 4-6 inch distance between actuator tip and the surface to be sprayed. Apply an even coat.

PACKAGING SPECIFICATIONS

Individual Unit					Case Pack						Pallet					
Appx Wt (oz)	W (in)	D (in)	Ht (in)	Cube	Case Pack	Appx Wt (lbs)	W (in)	D (in)	Ht (in)	Cube	Appx Wt (lbs)	Cases /Layer	Layers	Total QTY	Appx Ht (in)	Cube
1.04	2.598	2.598	8.66	0.033	6	6.60	5.56	8.12	9.25	0.24	1330	39	5	195	48.0	56.94

10oz. Spray & Stay Gel Lubricant 6 ct o/s	Case # / GTIN #: 1 00 79567 30010 3	ITEM # / UPC #: 0 79567 3001 6
---	-------------------------------------	--------------------------------

STORAGE

Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol.

DISPOSAL

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate containers.

SPECIAL USE WARNINGS

CONTENTS ARE EXTREMELY FLAMMABLE: Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. **ELECTRICITY CAN BURN A HOLE IN THE CAN AND CAUSE CONTENTS TO BURST INTO FLAMES.** To avoid serious burn injury, do not let **THE CAN** touch battery terminals, electrical connections on motors or appliances or any other source of electricity. **CONTENTS UNDER PRESSURE:** Do not puncture or incinerate (burn) container, even when empty. Do not expose to heat or store above 120°F. Avoid eye contact. Avoid prolonged or repeated contact with skin and clothing. Avoid breathing vapors or spray mists. Use in well ventilated area. Wash thoroughly with soap and water after use. Intentional inhalation abuse (concentrating and inhaling vapors) may be harmful or fatal. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID: CONTAINS PETROLEUM DISTILLATES AND PROPANE PROPELLANT

Ingestion (Swallowed): Do not induce vomiting unless directed to do so by medical personnel. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: Flush thoroughly with water for 15 minutes. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation persists, get medical attention.

Inhalation (Breathing): If irritation develops, discontinue use and move to fresh air. Get medical attention if irritation or other symptoms persist.

REGULATORY INFORMATION

U.S. Federal Regulations: CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III: Hazard Category For Section 311/312: Acute Health, Fire Hazard, Sudden Release of Pressure; **Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None; Section 302 Extremely Hazardous Substances (TPQ): None; **EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory; **Canadian WHMIS Classification:** Class B-5 (Flammable Aerosol), Class D-2-A (Very toxic material causing other chronic effects)



WD-40 COMPANY
PO BOX 80607, San Diego, CA 92138 USA
WD-40 Safety Hotline 1-888-324-7596
WD40Specialist.com



*Compared to WD-40 Multi-Use Product using independent lab test ASTM D-5620A

**Independent lab tests conducted in humidity chamber. Results vary depending on extreme conditions.