



# JOMAX<sup>®</sup> SPRAY ONCE<sup>®</sup> EXTERIOR STAIN REMOVER

## DESCRIPTION AND USES

JOMAX<sup>®</sup> Spray Once<sup>®</sup> Exterior Stain Remover is the simple way to remove tough stains from mold, mildew, moss and algae on exterior surfaces. Simply dilute as instructed, apply and walk away; no scrubbing or rinsing required. The bleach-free and non-acidic formula works with the rain and moisture over time to remove unwanted stains.

Spray Once is safe for porous and non-porous surfaces including siding, roofs, fences, decks, patios, driveways, walkways, brick, patio furniture and more.

## PERFORMANCE CHARACTERISTICS

- Removes stains from mold, mildew, moss & algae
- Safe for porous and non-porous surfaces
- No scrub, no rinse formula
- Can be used near plants and shrubs
- Easy application with a garden sprayer

## PRODUCTS

SKU	DESCRIPTION
308764	1 Gallon (Four Pack)
314755	1 Gallon (Two Pack)

## PRODUCT APPLICATION

### IMPORTANT

Read the entire label prior to application. Shake bottle vigorously before each use. Only apply to dry surfaces. Keep people and pets off treated surfaces until product has dried. Avoid runoff into waterways. Do not mix with any other chemicals.

### PREPARATION

Check the weather forecast to ensure there is no rainfall expected for at least 5 hours. For best results, apply on a cool day with minimal wind. Do not apply when the temperature is below 45°F (7°C).

## PRODUCT APPLICATION (cont.)

### DIRECTIONS

Rinse surrounding plants and grasses with water **before and after** application. Shake Spray Once concentrate thoroughly. Dilute 1 part concentrate to 4 parts water in a pump-up garden sprayer. See the dilution chart below.

SPRAY ONCE+	WATER =	CLEANING SOLUTION
¾ Cup	3 ¼ Cups	1 Qt.
3 ¼ Cups	12 ¾ Cups	1 Gal.
1 Gal.	4 Gal.	5 Gal.

Spray directly onto the dry surface, completely saturating the stains. Walk away; no scrubbing or rinsing required.

### RESULTS

In most cases, light stains will disappear within days but results will vary based on the severity of the stains and weather conditions. Severe stains could take several months before surface improvement is visible. A second application may be needed. However, clean-up the following season will be easier. Surfaces that have minimal exposure to the wind, rain and moisture may need light scrubbing or an additional application.

### COVERAGE

When diluted as instructed, one gallon of concentrate makes up to 5 gallons of cleaning solution and covers up to 1,500 square feet.

### FIRST AID

If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes and get medical attention. Remove contaminated clothing and wash it before use. If swallowed, do not induce vomiting. Get medical attention immediately.



**JOMAX® SPRAY ONCE®  
EXTERIOR STAIN REMOVER**

**PHYSICAL PROPERTIES**

		<b>SPRAY ONCE EXTERIOR STAIN REMOVER</b>
<b>Composition</b>		Proprietary Ingredients and Water
<b>Weight</b>	<b>Per Gallon</b>	8.34 lbs
	<b>Per Liter</b>	1.00 kg
<b>pH</b>		10
<b>VOC (Weight %)</b>		0.79
<b>Odor</b>		Ammonia like
<b>Practical Coverage</b>		Up to 1,500 square feet
<b>Shelf Life</b>		5 Years
<b>Flash Point</b>		>200°F (94°C)
<b>Warning!</b>		Contains quaternary ammonium salts and ethoxylated alcohols. Causes eye and skin burns. Do not get in eyes, on skin or clothing. Wear protective eyewear and gloves during use. Avoid breathing vapors or spray mist. Use only with adequate ventilation. Close container after each use. Wash hands thoroughly with soap and water after handling. In case of emergency, call your physician, local poison control center or local emergency room. For product health information call 847-367-7700. <b>KEEP OUT OF REACH OF CHILDREN.</b>
<b>Safety Information</b>		For Additional Information, See SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.