

# Safety Data Sheet



Revision Number: 002.0

Issue date: 04/07/2021

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** GE TUB AND TILE SILICONE KITCHEN AND BATH PROJECTS **IDH number:** 2749485  
**Product type/use:** Silicone Sealant  
**Restriction of Use:** None identified  
**Company address:** Henkel Corporation  
One Henkel Way  
Rocky Hill, Connecticut 06067  
**Region:** United States  
**Contact information:**  
Telephone: +1 (860) 571-5100  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
Internet: www.henkeln.com

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY
None	None

### PICTOGRAM(S)

None

### Precautionary Statements

**Prevention:** Not prescribed  
**Response:** Not prescribed  
**Storage:** Not prescribed  
**Disposal:** Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Silicon dioxide, crystalline	7631-86-9	>= 5 - <= 10

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

**Inhalation:** If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:** Wipe off with paper towel or cloth. Rinse with running water and soap. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse. Seek medical attention immediately.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical attention immediately.

IDH number: 2749485

Product name: GE TUB AND TILE SILICONE KITCHEN AND BATH PROJECTS  
Page 1 of 5

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek medical attention immediately.

**Symptoms:** See Section 11.

## 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

**Special firefighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Unusual fire or explosion hazards:** Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. In case of fire, keep containers cool with water spray.

**Hazardous combustion products:** Oxides of carbon. Oxides of silicon. Formaldehyde. Toxic and irritating vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

**Clean-up methods:** Ensure adequate ventilation. Wear appropriate personal protective equipment. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

## 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes, skin and clothing. Do not wear contact lenses. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Vapours should be extracted to avoid inhalation. Wash thoroughly after handling. See Section 8 of the SDS for Personal Protective Equipment. Use only with adequate ventilation. Keep container closed.

**Storage:** Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silicon dioxide, crystalline	6 mg/m <sup>3</sup> TWA	20 MPPCF TWA 0.8 mg/m <sup>3</sup> TWA	None	None

**Engineering controls:** Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Paste
<b>Color:</b>	Colorless
<b>Odor:</b>	Acetic acid
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	Not available.
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Not available.
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	2.30 %; 23 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of silicon. Formaldehyde.
<b>Incompatible materials:</b>	Acids and bases. Oxidizing agents. Amines.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Exposure to moisture.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit.
<b>Skin contact:</b>	May cause mild skin irritation. May cause allergic skin reaction.
<b>Eye contact:</b>	May cause eye irritation.
<b>Ingestion:</b>	Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silicon dioxide, crystalline	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg Inhalation LC50 (Rat, 4 h) = > 58.8 mg/l Inhalation LC50 (Rat, 4 h) = > 0.14 mg/l Inhalation LC50 (Rat, 4 h) = > 2.08 mg/l Inhalation LC50 (Rat, 4 h) = > 0.69 mg/l	Nuisance dust

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silicon dioxide, crystalline	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

**Information provided is for unused product only.**

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

<b>Proper shipping name:</b>	Not regulated
<b>Hazard class or division:</b>	None
<b>Identification number:</b>	None
<b>Packing group:</b>	None

### International Air Transportation (ICAO/IATA)

<b>Proper shipping name:</b>	Environmentally hazardous substance, solid, n.o.s. (octamethylcyclotetrasiloxane, 4,5-Dichloro-2-octyl-2H-isothiazol-3-one)
<b>Hazard class or division:</b>	9
<b>Identification number:</b>	UN 3077
<b>Packing group:</b>	III

### Water Transportation (IMO/IMDG)

<b>Proper shipping name:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (octamethylcyclotetrasiloxane, 4,5-Dichloro-2-octyl-2H-isothiazol-3-one)
<b>Hazard class or division:</b>	9
<b>Identification number:</b>	UN 3077
<b>Packing group:</b>	III
<b>Marine pollutant:</b>	octamethylcyclotetrasiloxane, 4,5-Dichloro-2-octyl-2H-isothiazol-3-one

## 15. REGULATORY INFORMATION

### United States Regulatory Information

<b>TSCA 8 (b) Inventory Status:</b>	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
<b>TSCA 12 (b) Export Notification:</b>	None above reporting de minimis
<b>CERCLA/SARA Section 302 EHS:</b>	None above reporting de minimis.
<b>CERCLA/SARA Section 311/312:</b>	None
<b>CERCLA/SARA Section 313:</b>	None above reporting de minimis.
<b>California Proposition 65:</b>	No California Proposition 65 listed chemicals are known to be present.

### Canada Regulatory Information

<b>CEPA DSL/NDSL Status:</b>	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
------------------------------	---

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 3, 8, 9

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 04/07/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.