

PRODUCT DESCRIPTION

Kool Seal® Premium Elastomeric Finish Coat (KS0063600) is formulated using a 100% acrylic polymer that provides outstanding adhesion and superior reflectivity. Formulated to resist cracking and peeling, Kool Seal® Premium Elastomeric Finish Coat provides excellent waterproofing capabilities.

FEATURES AND BENEFITS

- 10-year warranty
- 100% acrylic roof coating
- Renews most roofing substrates
- Expands and contracts with the roof
- Long-lasting protection and reflectivity

RECOMMENDED USES

- Metal, single ply, smooth BUR, modified bitumen, polyurethane foam, concrete, existing asphaltic and elastomeric roof coatings and other approved surfaces.
- NOT for use on roof shingles

ORDERING INFORMATION

Part Number	Color/Size
KS0063600-16	White (0.9 Gallon)
KS0063600-20	White (4.75 Gallon Pail)

PRODUCT CHARACTERISTICS

Technology	100% Acrylic
Color	White
Volume Solids	45% ± 2%
Weight Solids	58% ± 2%
VOC	< 50 g/L
Drying Time	Exposure to rain or heavy dew: 4-6 hours Between coats and before foot traffic: 24 hours minimum
<i>Dry time is temperature, humidity and film thickness dependent</i>	

COVERAGE RATES (Per coat, two coats recommended):

Metal: 70-100 sq. ft/gallon

Apply the following substrates with Kool Seal® Elastomeric Base Coat at 50-100 sq. ft/gallon, followed by Kool Seal® Elastomeric Finish Coat at the following rates:

Single Ply: 50-70 sq. ft/gallon

Smooth BUR/Modified Bitumen: 50-70 sq. ft/gallon

Polyurethane Foam: 50-70 sq. ft/gallon

Concrete: 50 sq. ft/gallon

DO NOT THIN.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in U.S.) or contact your local health authority.

Surface must be power washed (minimum 2,000 psi) to remove dirt and other foreign matter that could prevent proper adhesion. Surfaces must be completely dry prior to coating. **IMPORTANT: Where ponding water conditions persist beyond 48 hours, roof drains or other corrective measures must be installed to eliminate water buildup prior to coating the roof.** Repair all cracks, breaks, open seams and other imperfections with Kool Seal® Storm Patch® Acrylic Patching Cement and Kool Seal® Storm Patch® Polyester Fabric. Apply Kool Seal® Storm Patch® Acrylic Rust Primer to existing rusted areas.

APPLICATION

Do not apply below 50°F (10°C) or when rain is forecast. Applications during periods of low temperature and high humidity will extend dry time. **KEEP FROM FREEZING.**

Thoroughly mix product prior to application. Airless spray or apply with a low nap roller or broom at the appropriate coverage rate. Allow adequate drying time between coats. Two coats recommended. For specific application guidelines, call 888-321-KOOL (5665).

CLEANUP

Warm, soapy water.

CAUTIONS

- Use with adequate ventilation.
- Keep out of the reach of children.
- Use a NIOSH-approved respirator, when necessary.
- Do not take internally.
- In case of ingestion, CALL A PHYSICIAN immediately. DO NOT induce vomiting.
- If splashed in the eyes, flush thoroughly with clean water for a minimum of 15 minutes. CALL A PHYSICIAN immediately. May cause irritation to the skin. If brought into contact with the skin, wash thoroughly with soap and water. Seek medical attention if redness or irritation occurs. Avoid breathing vapors and spray mist. Reseal container after each use. Wear protective clothing, gloves and goggles. Read MSDS before using product.

LIMITED WARRANTY

For 10 years from date of purchase, if this product fails to perform in accordance with the specifications set forth on this label when applied according to label directions, as your sole and exclusive remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. This warranty is made to the original purchaser only and is not transferable. This warranty excludes failure due to improper surface preparation, structural defects, or failure of other previously applied products. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

TECHNICAL SERVICES

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of KST Coatings and The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your KST or Sherwin-Williams representative to obtain the most recent Product Data Sheet.